

SHUTTING DOWN THE GENESIS DOME

TELESCOPE

1. UNDER THE UTILITIES MENU CHOOSE 'PARK SCOPE' AND 'HOME POSITION'
2. REPLACE THE LENS COVER ON TELESCOPE
3. REPLACE THE LENS COVER ON THE FINDERSCOPE
4. REMOVE THE EYEPIECE AND PUT COVER IN PLACE
5. PLACE THE COVER BACK OVER THE TELESCOPE
6. WHEN THE HANDSET SAYS 'TURN POWER OFF' SWITCH POWER OFF TO MOUNT AND REMOVE HANDSET
7. PLACE THE HANDSET AND ALL EYEPIECES BACK IN THE CASE AND CLOSE

DOME

1. ROTATE DOME ROOF IF NECESSARY TO GET HOLD OF ROPE FROM LOWER FLAPS AND THEN PULL BOTH ROPES SIMULTANEOUSLY TO CLOSE THE FLAP
2. PULL EACH ROPE TAUGHT AND PLACE INTO CLEAT
3. WRAP ROPE ROUND HITCH IN FIGURE OF 8 WITH LOCKING LOOP AT END
4. GATHER UP LOOSE ROPE AND THROW ONTO LEDGE
5. USING STRAP, CAREFULLY CLOSE UPPER SLIT ENSURING YOU CONTROL THE WEIGHT AND MOTION TO AVOID DAMAGE
6. ROTATE ROOF TO ENSURE THAT THE SLIT IS OVER THE STAIRWELL
7. TURN OFF POWER TO DOME ROOF (SOCKET ON COUNTER)
8. REMOVE ALL BELONGINGS AND EYEPIECE CASE
9. TURN OFF ALL LIGHTS
10. CLOSE AND LOCK THE DOOR

11. RETURN THE KEY TO THE KEYSAFE AND PLACE THE EYEPiece CASE IN THE CUPBOARD IN THE SECURE STORE

